	CONDUIT			SIGNAL	EQUIPMENT
<u>NEW</u>	EXISTING	LIGHTING CONDUIT, UNLESS OTHERWISE	<u>NEW</u>	EXISTING	
		INDICATED OR NOTED TRAFFIC SIGNAL CONDUIT		コトー	PEDESTRIAN SIGNAL HEAD
	c	COMMUNICATION CONDUIT TELEPHONE CONDUIT	0	(1)	PUSH BUTTON ASSEMBLY POST
— F — —	- — f — —	FIRE ALARM CONDUIT		⊢ - ⊣	PEDESTRIAN BARRICADE
——FO——————————————————————————————————	- — fo — — —	FIBER OPTIC CONDUIT CONDUIT TERMINATION	◄-	<h -<="" td=""><td>VEHICLE SIGNAL HEAD (WITH BACKPLATE)</td></h>	VEHICLE SIGNAL HEAD (WITH BACKPLATE)
R	O	CONDUIT RISER ATTACHED TO THE STRUCTURE OR SERVICE POLE	⊿ ◄⊢	_1+_1+ -	VEHICLE SIGNAL HEAD WITH ANGLE VISOR
NEW		EQUIPMENT	₽V	~J+ - PV	MODIFICATIONS OF BASIC SYMBOL: "L" INDICATES ALL NON-ARROW SECTIONS LOUVERED "LG" INDICATES ALU 12" SECTIONS PROGRAMMED VISIBILITY "8" INDICATES ALL 12" SECTIONS PROGRAMMED VISIBILITY "8" INDICATES ALL 8" SECTIONS (ONLY WHEN SPECIFIED)
<u>NEW</u>	EXISTING	OVERHEAD LINES			"8" INDĪCĀTĒS ALL 8" SECTIONS (ONLY WHEN SPĒCIFĪĒD) -
	ا_ آ_ n	WOOD POLE, "U" INDICATES UTILITY OWNED	→	~A -	VEHICLE SIGNAL HEAD CONSISTING OF RED, YELLOW AND GREEN LEFT ARROW SECTIONS
((POLE GUY WITH ANCHOR	◄ ₩,	~>#_→	VEHICLE SIGNAL HEAD CONSISTING OF RED AND YELLOW SECTIONS WITH AN UP GREEN ARROW SECTION
	لا کیا	UTILITY TRANSFORMER - GROUND MOUNTED	◄ ₩─	∼朮 −	VEHICLE SIGNAL HEAD (5 SECTION) CONSISTING OF RED, YELLOW AND GREEN SECTIONS WITH YELLOW AND GREEN RIGHT ARROW SECTIONS
	<u></u>	SERVICE EQUIPMENT ENCLOSURE TYPE. DOOR INDICATES FRONT OF ENCLOSURE	$\overset{\bullet}{\longleftarrow}$	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~	TYPE 15TS STANDARD WITH VEHICLE SIGNAL HEAD AND LUMINAIRE
T	[+]	TELEPHONE DEMARCATION CABINET		`34 ∭ −−3>	TYPE 21TS STANDARD WITH VEHICLE SIGNAL HEAD AND LUMINAIRE
POLE-	-MOUNTED S	ERVICE DESIGNATION	FXX	£	STANDARD WITH LUMINAIRE AND SIGNAL MAST ARMS AND ATTACHED VEHICLE SIGNAL HEADS
TYPE H	SERVICE, 28'-10"	TYPE OF INSTALLATION AND POLE HEIGHT ABOVE GRADE	***	~HD	TYPE 1 STANDARD WITH ATTACHED VEHICLE SIGNAL HEADS
FLASHING BEACON			£ -= 5	STANDARD WITH A SIGNAL MAST ARM, ATTACHED VEHICLE SIGNAL HEADS AND INTERNALLY ILLUMINATED STREET NAME SIGN	
NEW	EXISTING		⊠ ⁄	23/	CONTROLLER ASSEMBLY, DOOR INDICATES FRONT OF CABINET
R ·∭	R-Ÿπ —	FLASHING BEACON (ONE VEHICLE SIGNAL HEAD WITH BACKPLATE AND VISOR) "R" INDICATES RED INDICATION, "Y" INDICATES YELLOW INDICATION		∠ 5′	
Y ∄ ↓	۱۲ × ۲ ایار ۱۳۰۰ ۲ ۲ ۲ ۲	FLASHING BEACON WITH TYPE 15-FBS STANDARD AND A SIGN.			
R R	トン マン	FLASHING BEACON WITH TYPES 9, 9A OR 9B UNLESS OTHERWISE SPECIFIED OR INDICATED	SIGN		DATED



REGISTERED ELECTRICAL ENGINEER

ROUTE POST MILES SHEET TOTAL TOTAL PROJECT NO. SHEETS

Hamid Zolfaghari

SIGNAL EQUIPMENT Cont

Dist COUNTY

<u>NEW</u>	EXISTING	
•	0	GUARD POST
	о – – -[_	TYPE 1 STANDARD WITH RAMP METERING SIGN
—◀	\longrightarrow	OPTICAL DETECTOR FOR THE EMERGENCY VEHICLE DETECTION

NOTES:

- All signal sections shall be 12" unless shown otherwise.
- 2. Signal heads shall be provided with backplates unless shown otherwise.

ILLUMINATED OVERHEAD SIGN

<u>NEW</u>	<u>EXISTING</u>	
0	<u>_</u>	SINGLE POST, SINGLE ILLUMINATED SIGN, BALANCED BUTTERFLY
þ	<u> </u>	SINGLE POST, DOUBLE ILLUMINATED SIGN, BALANCED BUTTERFLY
	1 ₁ 1 ₃	SINGLE POST, SINGLE ILLUMINATED SIGN, FULL CANTILEVER
	ار اح	DOUBLE POST, SINGLE ILLUMINATED SIGN
	<u> </u>	SINGLE ILLUMINATED SIGN MOUNTED ON STRUCTURE
	.d .d×.	DOUBLE POST, SINGLE ILLUMINATED SIGN WITH ELECTROLIER

STATE OF CALIFORNIA DEPARTMENT OF TRANSPORTATION

ELECTRICAL SYSTEMS (LEGEND)

NO SCALE

RSP ES-1B DATED JULY 21, 2017 SUPERSEDES STANDARD PLAN ES-1B DATED OCTOBER 30, 2015 - PAGE 419 OF THE STANDARD PLANS BOOK DATED 2015.

REVISED STANDARD PLAN RSP ES-1B